Absorb-Rite® Bags

Offers a Two-in-One Design

The Absorb-Rite® filter bag from The Strainrite Companies substantially reduces oil and grease from aqueous based liquids. The Absorb-Rite® bag offers a unique two-in-one design that forces the liquid through the entire length of the filter, therefore uniformly utilizing all the absorbant media. Typically, this unique filter absorbs 10-15 times its weight in oil. The Absorb-Rite® offers in excess of 50% more absorbency than competing brands.

Features & Benefits

- Unique three layer construction results in maximum exposure time at minimum flow rate
- The top disc pre-filter material removes dirt and other particulate material prior to the adsorption of hydrocarbons
- Designs available to remove particles in the 1-200 micron range
- Absorb-Rite® has higher hydrocarbon removal capacity than other filter bags on the market
- Has higher capacity than most other bags on the market
- Standard bags fit SRID and SRHD filter vessels (fit competitor housings as well)
- Designed to minimize contamination during changeover

Applications

- Electroplating Paints
- Liquid Fertilizers
- Electroplating
- Pickling Liquids
- Cutting Oil Removal
- Waste Water Treatment
- Glycols

Ordering Information

		Example:
Material	SP - Polypropylene Felt	SP
Micron Rating	1, 5, 10, 25, 50, 75, 100, 200	100
Finish	S - Singed	S
Size	1 - 7" x 16" 2 - 7" x 30.5" 3 - 4.08" x 8" 4 - 4.08" x 14" *30 - 4.118" x 10" *65 - 4.118" x 22" *C1 - 7" x 16.5" *C2 - 7" x 31"	2
Ring	S - Carbon Steel SS - Stainless Steel P - Polypro Flange PR - Polypro Ring	S
Options	C - Absorb-RIte	C

*Not Available with Polypro Ring

SP100S2SC

Available to Fit All Bag Filter Housings

Anywhere oil or grease must be separated and removed from an industrial stream, Absorb-Rite® bags are designed to fill the need.

Best results at low flow rates to achieve longer contact time.

- #2 Size = 5 gpm
- #1 Size = 2½ gpm
- Estimate flows depending upon ppm oil and viscosity

Your Local Distributor

970 Calle Negocio
San Clemente, CA 92673
info@clearsolutionscorp.com
(949) 429-8922 ph
www.clearsolutionscorp.com