Rubber Fab

a Garlock Hygienic Technologies company

Authorized Distributor

CLEAR SOLUTIONS, INC.
Process Filtration and Fluid Handling Products

970 Calle Negocio
San Clemente, CA 92673
info@clearsolutionscorp.com
(949) 429-8922 ph
www.clearsolutionscorp.com

Sani-Lock®

Hose ID Inch	Part Number	Description	Fitting ID Inch	Flange Diameter Inch	Fitting Overall Length
1/2	08BWT-08SL-SS	.5in Buttweld x .5in Sani-Lock® Mini Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.36	1.23	1.73
1/2	08HB-08SL-SS	.5in Hose Barb x .5in Sani-Lock® Mini Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.30	1.23	2.98
3/4	12BWT-12SL-SS	.75in Buttweld x .75in Sani-Lock® Mini Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.63	1.23	1.73
3/4	12HB-12SL-SS	.75in Hose Barb x .75in Sani-Lock® Mini Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.62	1.23	3.23
1	16BWT-16SL-SS	1in Buttweld x 1in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.87	2.43	2.65
1	16HB-16SL-SS	1in Hose Barb x 1in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	0.87	2.43	3.40
1.5	24BWT-24SL-SS	1.5in Buttweld x 1.5in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	1.37	2.43	2.65
1.5	24HB-24SL-SS	1.5in Hose Barb x 1.5in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	1.36	2.43	5.24
2	32BWT-32SL-SS	2in Buttweld x 2in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	1.87	2.96	3.15
2	32HB-32SL-SS	2in Hose Barb x 2in Sani-Lock® Tri-Clamp® w/Locking Ears, 316SS, w/Tuf-Flex® Gasket	1.75	2.96	5.89

Sani-Lock® Fitting/Adapter Configuration Options

Sanitary

BSN – Bevel Seat Nut
MBS – Male Bevel Seat
FIL – Female I-Line
MIL – Male I-Line
JPF – John Perry Female
JPM – John Perry Male
QL – Q-Line
RTC – Reusable Tri-Clamp®

Pipe Thread (NPT)

FPT – Female Pipe Thread
MPT – Male Pipe Thread

Compression

CTA – Compression Tube Adapter
CTAFN – Compression Tube Adapter Ferrule and Nut
CTCFN – Compression Tube Connector Ferrule and Nut
CTC – Compression Tube Connector

JIC

FJIC – Female JIC
MUA – Male Union Adapter
FUA – Female Union Adapter

150# Flanges

LJF – LAP Joint Flange

Cam and Groove

FCL – Female Camlock
MCL – Male Camlock

All Sani-Lock® fittings are shipped with a complimentary Tuf-Flex® gasket.